

Entratek Wallbox Power Dot Eco

Innovativeness

- Minimal size, streamline design
- Home use with intelligent control

Secure and Safe

- 6mA DC residual current protection
- Anti-welding protection

Intelligent Control

- Wireless communication (Wi-Fi/Bluetooth)
- OCPP communication protocol

Flexible Option

- Type 2 charging cable
- RFID authentication or plug and play
- Wall-mount or floor-stand installation



Entratek Wallbox Power Dot Eco

Datasheet	Model	Entratek Wallbox Power Dot Eco
Input	Power Supply	3P+N+PE
	Rated Voltage	400V AC
	Rated Current	16A
	Frequency	50/60Hz
Output	Output Voltage	400V AC
	Maximum Current	16A
	Rated Power	11kW
User Interface	Charge Connector	Type 2 cable
	Cable Length	4m
	Enclosure	Plastic PC940
	LED Indicator	Green/Yellow/Red
	RFID Reader	Mifare ISO/IEC 14443 A
Communication	Start Mode	Plug&Play/RFID card
	Wi-Fi	Yes
	Bluetooth	Optional
Safety	OCPP	OCPP 1.6 Json (OCPP 2.0 optional)
	Energy Meter	No
	RCD	6mA DC
	Ingress Protection	IP65
	Impact Protection	IK10
	Warranty	2 years
	Electrical Protection	Over current protection, Residual current protection, Ground protection, Surge protection, Over/Under voltage protection, Over/Under frequency protection, Over/Under temperature protection
	Certification	CE
Certification Standard	EN/IEC 61851-1: 2017, EN/IEC 61851-21-2: 2018	
Environment	Installation	Wall-mount/Pole-mount
	Work Temperature	-30°C~+50°C
	Work Humidity	5%~95%
	Work Altitude	<2000m
Package	Product Dimension	325*181*87mm (H*W*D)
	Package Dimension	434*324*210mm (L*W*H)
	Net Weight	3.2kg
	Gross Weight	4.0kg
	External Package	Carton