

Entratek Wallbox Power Dot Pro

Innovativeness

- LED screen with status indication
- Modern design with intelligent control

Secure and Safe

- 6mA DC residual current protection
- Emergency Stop button

Intelligent Control

- Wireless communication
- OCPP communication protocol
- Smart charging or scheduled charge

Flexible Option

- Type 2 charging cable or socket
- RFID authentication or plug and play
- Wall-mount or floor-stand installation



Entratek Wallbox Power Dot Pro

Datasheet	Model	Entratek Wallbox Power Dot Pro
Input	Power Supply	3P+N+PE
	Rated Voltage	400V AC
	Rated Current	16A
	Frequency	50/60Hz
Output	Output Voltage	400V AC
	Maximum Current	16A
	Rated Power	11kW
User Interface	Charge Connector	Type 2 cable
	Cable Length	5m
	Human-Computer Interaction	LED screen
	LED Indicator	Yes
	RFID Reader	Yes
	Start Mode	Plug&Play/RFID
	Emergency Stop	Yes
Communication	Wi-Fi	Yes
	Ocpp	Ocpp 1.6 Json
Safety	RCD	6mA DC
	Protection Level	IP55 (storage), IP54 (connected with vehicle)
	Certification	CE
	Electrical Protection	Over current protection, Lightning protection, Over/Under voltage protection, Leakage protection, Over/Under temperature protection
	Certification Standard	EN 61851-1 & EN 61851-22
	Warranty	2 years
Environment	Installation	Wall-mount/Pole-mount
	Standby Power Consumption	2W
	Work Temperature	-30°C~+50°C
	Work Humidity	5%~95%
	Work Altitude	<2000m
Package	Product Dimension	234*343*115mm (H*W*D)
	Net Weight	5kg